



# ArrowADVANTAGE<sup>5</sup>™ Pressure Injectable PICC Set

with Blue FlexTip® Catheter and  
130 cm Platinum Tipped, Stainless Steel Marked Wire


Distal Lumen  
VasoNova™ VPS™  
compatible††

## REF PR-35041-HPSL

### Contents:

- ① 1: Indwelling Catheter: 4 Fr. x 50 cm Radiopaque **Pressure Injectable** Polyurethane with Blue FlexTip®, Extension Line Clamp and Protection Sleeve
- ② 1: Peel-Away Sheath: 15 Ga. x 4" (10 cm) Radiopaque over 4 Fr. Dilator
- ③ 1: Spring-Wire Guide, Marked: .018" (0.46 mm) dia. x 51-3/16" (130 cm) (Straight Soft Tip on One End - Straight Stiff Tip on Other)
- ④ 1: Spring-Wire Guide: .018" (0.46 mm) dia. x 17-3/4" (45 cm) (Straight Soft Tip on Both Ends)
- ⑤ 1: Introducer Needle: Echogenic 21 Ga. x 2-3/4" (7 cm) TW
- ⑥ 1: Syringe: 5 mL Luer-Lock  
1: Foil-Laminated Pouch 79% Skin Protectant Prep Pad  
1: Dust Cap: Non-Vented
- ⑦ 1: Clamp: Catheter
- ⑧ 1: Fastener: Catheter Clamp  
1: Chart Sticker  
1: Checklist/CLIP Sheet  
1: Flow Rate Information Card with Injection Log  
1: Patient ID Card  
1: Patient Information Booklet
- ⑨ 1: Dressing: STATLOCK®<sup>1</sup> Catheter Stabilization Device  
1: Paper Tape Measure

<sup>1</sup>A registered trademark of C. R. Bard, Inc.



STERILE EO



**Rx only. Warning: Read all package insert warnings, precautions, and instructions prior to use. Failure to do so may result in severe patient injury or death.**

Sterile. Single use – do not resterilize. Sterilized by ethylene oxide. Do not use if package has been previously opened or damaged. Does not contain natural rubber latex. Fluid path components are non-pyrogenic. Contains no medication.

††Meets VasoNova™ VPS™ stylet requirements for use.



Lumen	Priming Volume* (mL)	Flow Rate† (mL/hr)	Pump Flow Rate‡ (mL/hr)	MAX Pressure Injection Flow Rate** (mL/sec)
Distal (17 Ga.)	0.55	1220	5740	5

\* Priming volumes are approximate and are done without injection caps.

† Flow rates were determined using room temperature water, 100 cm head height and represent approximate flow capabilities.

‡ Pump flow rates are determined at maximum pump pressure of 10 psig and represent approximate flow capabilities.

\*\*Pressure injection flow rates are determined at the injector pressure setting of 300 psi maximum using media of 11.8 centipoise viscosity, with 152 cm pressure tubing.

**ARROW**  
INTERNATIONAL

2400 Bernville Road  
Reading, PA 19605 USA  
[www.arrowintl.com](http://www.arrowintl.com)

IR-35041-101C (6/16)



## ArrowADVANTAGE<sup>5</sup>™ Pressure Injectable PICC Set

4 Fr. | 50 cm catheter length | .018 inch dia. spring-wire guide

Distal Lumen  
VasoNova™ VPS™  
compatible††

REF PR-35041-HPSL

**ARROW**  
INTERNATIONAL

Peel to OPEN