



ArrowADVANTAGE⁵™ Pressure Injectable PICC Set

with Blue FlexTip® Catheter and
80 cm Platinum Tipped, Stainless Steel Marked Wire


Distal Lumen
VasoNova™ VPS™
compatible††

REF PR-35541-HPSM

Contents:

- ① 1: Indwelling Catheter: 4 Fr. x 55 cm Radiopaque **Pressure Injectable** Polyurethane with Blue FlexTip®, Extension Line Clamp and Protection Sleeve
- ② 1: Peel-Away Sheath: 15 Ga. x 4" (10 cm) Radiopaque over 4 Fr. Dilator
- ③ 1: Spring-Wire Guide, Marked: .018" (0.46 mm) dia. x 31-1/2" (80 cm) (Straight Soft Tip on One End - Straight Stiff Tip on Other)
- ④ 1: Spring-Wire Guide: .018" (0.46 mm) dia. x 17-3/4" (45 cm) (Straight Soft Tip on Both Ends)
- ⑤ 1: Introducer Needle: Echogenic 21 Ga. x 2-3/4" (7 cm) TW
- ⑥ 1: Syringe: 5 mL Luer-Lock
1: Foil-Laminated Pouch 79% Skin Protectant
Prep Pad
1: Dust Cap: Non-Vented
- ⑦ 1: Clamp: Catheter
- ⑧ 1: Fastener: Catheter Clamp
1: Chart Sticker
1: Checklist/CLIP Sheet
1: Flow Rate Information Card with Injection Log
1: Patient ID Card
1: Patient Information Booklet
- ⑨ 1: Dressing: STATLOCK®¹
Catheter Stabilization Device
1: Paper Tape Measure

¹ A registered trademark of C. R. Bard, Inc.



STERILE EO



Rx only. Warning: Read all package insert warnings, precautions, and instructions prior to use. Failure to do so may result in severe patient injury or death.

Sterile. Single use – do not resterilize. Sterilized by ethylene oxide. Do not use if package has been previously opened or damaged. Does not contain natural rubber latex. Fluid path components are non-pyrogenic. Contains no medication.

††Meets VasoNova™ VPS™ stylet requirements for use.



Lumen	Priming Volume* (mL)	Flow Rate† (mL/hr)	Pump Flow Rate‡ (mL/hr)	MAX Pressure Injection Flow Rate** (mL/sec)
Distal (17 Ga.)	0.58	1140	5720	5

* Priming volumes are approximate and are done without injection caps.

† Flow rates were determined using room temperature water, 100 cm head height and represent approximate flow capabilities.

‡ Pump flow rates are determined at maximum pump pressure of 10 psig and represent approximate flow capabilities.

**Pressure injection flow rates are determined at the injector pressure setting of 300 psi maximum using media of 11.8 centipoise viscosity, with 152 cm pressure tubing.

ARROW
INTERNATIONAL

2400 Bernville Road
Reading, PA 19605 USA
www.arrowintl.com

IR-35541-100C (6/16)



ArrowADVANTAGE⁵™ Pressure Injectable PICC Set

4 Fr. | 55 cm catheter length | .018 inch dia. spring-wire guide

Distal Lumen
VasoNova™ VPS™
compatible††

REF PR-35541-HPSM

ARROW
INTERNATIONAL

