



REF AK-24301-SK

16 Ga. 1 Lumen 20 cm catheter length .032 inch dia. spring-wire guide

Arrowg+ard Blue® One-Lumen CVC

Contents:

- 1: Arrowg+ard Blue® One-Lumen Catheter: 16 Ga. (1.8 mm OD) x 20 cm

1: Spring-Wire Guide, Marked: .032" (0.81 mm) dia. x 23-5/8" (60 cm) (Straight Soft Tip on One End - "J" Tip on Other) with Arrow Advancer

1: Catheter: 18 Ga. x 2-1/2" (6.35 cm) Radiopaque over 20 Ga. RW Introducer Needle

1: Injection Needle: 25 Ga. x 1" (2.54 cm)

1: Blunt Fill Needle: 18 Ga. x 1-1/2" (3.81 cm)

1: Pressure Transduction Probe

1: Introducer Needle: 18 Ga. x 2-1/2" (6.35 cm) XTW and 5 mL Arrow® Raulerson Spring-Wire Introduction Syringe

1: Injection Needle: 22 Ga. x 1-1/2" (3.81 cm) and 5 mL Luer-Slip Syringe

1: Syringe: 3 mL Luer-Lock

1: Tissue Dilator: 7 Fr. (2.3 mm) x 10.2 cm

1: 5 mL 1% Lidocaine HCl Solution and Alcohol Prep

1: 3 mL Applicator 2% CHG and 70% IPA ChloraPrep®¹ One-Step Solution with Hi-Lite Orange™ Tint

1: Dust Cap: Non-Vented

1: SecondSite™ Adjustable Hub: Fastener

1: SecondSite™ Adjustable Hub: Catheter Clamp

1: SharpsAway® II Locking Disposal Cup
- 1: SharpsAway® Disposal Cup


1: Drape: 41" x 50" with 4" fenestration, with adhesive

1: Safety Scalpel: #11

3: Gauze Pad: 4" x 4" (10 cm x 10 cm)

1: Suture: 3-0 Braided Silk with Straight Needle
- ¹A registered trademark of CareFusion or one of its subsidiaries.

Rx only
Warning: Read all package insert warnings, precautions, and instructions prior to use. Failure to do so may result in severe patient injury or death.
California Prop. 65
⚠ **WARNING:** Cancer and Reproductive Harm.
www.P65Warnings.ca.gov
Not made with natural rubber latex.
Store between 20 – 25°C (68 – 77°F).
Sterilized using ethylene oxide unless otherwise indicated in the contents list.
Fluid path components are non-pyrogenic.
Contraindications: The Arrowg+ard Blue antimicrobial catheter is contraindicated for patients with known hypersensitivity to chlorhexidine, silver sulfadiazine and/or sulfa drugs.

 Lumen	Priming Volume* (mL)	Gravity Flow Rate† (mL/hr)
Distal (16 Ga.)	0.44	2781

* Priming volumes are approximate and are done without accessories.
† Flow rate values are approximate and are determined using deionized water at 100 cm head height.



Arrow International LLC
Subsidiary of Teleflex Incorporated
3015 Carrington Mill Blvd.
Morrisville, NC 27560 USA

Teleflex®
www.teleflex.com

LBL051028 R01 (2022-02)



REF AK-24301-SK

16 Ga. 1 Lumen 20 cm catheter length .032 inch dia. spring-wire guide

Arrowg+ard Blue® One-Lumen CVC