



REF ASK-15703-SPH (IPNXXXXXX)



7 Fr. 3 Lumen

20 cm catheter length

.032 inch dia. spring-wire guide

Pressure Injectable Three-Lumen CVC Kit



Contents:

- | | |
|--|--|
| 1: Three-Lumen Catheter: 7 Fr. (2.5 mm OD) x 20 cm, Pressure Injectable | 2: Gauze Pad: 2" x 2" (5 cm x 5 cm) |
| 1: Spring-Wire Guide, Marked: .032" (0.81 mm) dia. x 23-5/8" (60 cm) (Straight Soft Tip on One End - "J" Tip on Other) with Arrow Advancer | 5: Gauze Pad: 4" x 4" (10 cm x 10 cm) |
| 1: Catheter: 18 Ga. x 2-1/2" (6.35 cm) Radiopaque over 20 Ga. RW Introducer Needle | 1: Surgical Apparel: Impervious Gown |
| 1: Pressure Transduction Probe | 1: Dressing: I.V. Advanced 8.5 cm x 11.5 cm |
| 1: Introducer Needle: Echogenic 18 Ga. x 2-1/2" (6.35 cm) XTW and 5 mL Arrow® Raulerson Spring-Wire Introduction Syringe | 1: Surgical Apparel: Bouffant Cap |
| 1: Injection Needle: Eclipse™ ¹ 23 Ga. x 1-1/2" (3.81 cm) and 5 mL Luer-Slip Syringe | 1: Surgical Apparel: Mask with Eye Shield |
| 1: Injection Needle: Eclipse™ ¹ 25 Ga. x 1" (2.54 cm) and 3 mL Luer-Lock Syringe | 1: Suture: 3-0 Silk with Curved Needle |
| 1: Syringe: 10 mL Luer-Lock | 3: Valve: MaxZero™ ² Needleless Connector |
| 1: Tissue Dilator: 8.5 Fr. (2.8 mm) x 10.2 cm | 1: HemoHopper® Fluid Receptacle |
| 1: SecondSite™ Adjustable Hub: Fastener | ¹ A trademark of Becton, Dickinson and Company. |
| 1: SecondSite™ Adjustable Hub: Catheter Clamp | ² A trademark of CareFusion or one of its subsidiaries. |
| 1: SharpsAway® II Locking Disposal Cup | |
| 1: SharpsAway® Disposal Cup | |
| 1: Maximal Barrier Drape™ with 4" fenestration | |
| 1: Towel | |
| 1: Needle Holder | |
| 1: Safety Scalpel: #11 | |
| 1: Checklist/CLIP Sheet | |
| 1: Sterile Procedure Sign | |
| 2: Gauze Pad: 3" x 3" (7.6 cm x 7.6 cm) | |

Not made with natural rubber latex.



Lumen

Priming Volume[†] (mL)Gravity Flow Rate[†] (mL/hr)MAX Pressure Injection Flow Rate^{**} (mL/sec)

Distal (16 Ga.)	0.47	2656	10
Medial (18 Ga.)	0.40	1245	5
Proximal (18 Ga.)	0.42	1328	5

* Priming volumes are approximate and are done without accessories.

† Flow rate values are approximate and are determined using deionized water at 100 cm head height.

** Pressure injection flow rates are determined using media of 11.8 centipoise (cP) viscosity, with 152 cm administration set tubing.

