



REF CS-16553-J

5.5 Fr. 3 Lumen

13 cm catheter length

.018 inch dia. spring-wire guide

Three-Lumen CVC

Contents:

- 1: Three-Lumen Catheter: 5.5 Fr. (1.9 mm OD) x 13 cm
- 1: Spring-Wire Guide: .018" (0.46 mm) dia. x 17-3/4" (45 cm) (Straight Soft Tip on One End - "J" Tip on Other)
- 1: Catheter: 22 Ga. x 1-3/4" (4.45 cm) Radiopaque over 25 Ga. RW Introducer Needle
- 1: Introducer Needle: 21 Ga. x 1-1/2" (3.81 cm) TW
- 1: Syringe: 5 mL Luer-Slip
- 1: Tissue Dilator: 6 Fr. (2.0 mm) x 7.6 cm
- 1: Tissue Dilator: 6 Fr. (2.0 mm) x 4.1 cm
- 3: Dust Cap: Non-Vented
- 1: SecondSite™ Adjustable Hub: Fastener
- 1: SecondSite™ Adjustable Hub: Catheter Clamp

All components are CE 2797 unless otherwise noted.

Rx only

Warning: Read all package insert warnings, precautions, and instructions prior to use. Failure to do so may result in severe patient injury or death. www.teleflex.com/IFU

Not made with natural rubber latex.
Fluid path components are non-pyrogenic.



CAS # 7440-48-4



Lumen	Priming Volume* (mL)	Gravity Flow Rate† (mL/hr)
Distal (20 Ga.)	0.32	988
Medial (22 Ga.)	0.38	370
Proximal (22 Ga.)	0.34	422

* Priming volumes are approximate and are done without accessories.

† Flow rate values are approximate and are determined using deionized water at 100 cm head height.

EU Authorized Representative and Importer:

Teleflex Medical
IDA Business and Technology Park
Dublin Road, Athlone
Co. Westmeath, Ireland

Arrow International LLC
Subsidiary of Teleflex Incorporated
3015 Carrington Mill Blvd.
Morrisville, NC 27560 USA

Teleflex®
www.teleflex.com

LBL055273 R01 (2023-10)

LOT



5.5 Fr. 3 Lumen

13 cm catheter length

.018 inch dia. spring-wire guide

REF CS-16553-J

Three-Lumen CVC