



REF EU-14955-CVT

9.5 Fr. 5 Lumen 30 cm catheter length .032 inch dia. spring-wire guide

# Five-Lumen CVC

**Contents:**

- 1: Five-Lumen Catheter: 9.5 Fr. (3.3 mm OD) x 30 cm
- 1: Spring-Wire Guide, Marked: .032" (0.81 mm) dia. x 26-3/4" (68 cm) (Straight Soft Tip on One End - "J" Tip on Other) with Arrow Advancer with ECG Mark
- 1: Introducer Needle: Echogenic 18 Ga. x 2-1/2" (6.35 cm) XTW
- 1: Syringe: 5 mL Luer-Slip
- 1: Tissue Dilator: 10 Fr. (3.5 mm) x 10.2 cm
- 1: ECG Extension Cable
- 5: Dust Cap: Non-Vented
- 1: SecondSite™ Adjustable Hub: Fastener
- 1: SecondSite™ Adjustable Hub: Catheter Clamp
- 1: Scalpel: #11

**Warning: Read all package insert warnings, precautions, and instructions prior to use. Failure to do so may result in severe patient injury or death. [www.teleflex.com/IFU](http://www.teleflex.com/IFU)**  
**Not made with natural rubber latex.**  
 Fluid path components are non-pyrogenic.

All components are CE 2797 unless otherwise noted.



CAS # 7440-48-4

- en
- be
- bg
- hr
- cs
- da
- nl
- et
- fi
- fr
- de
- el
- hu
- is
- it
- lv
- lt
- no
  
- pl
- pt
- ro
- ru
- sr
- sk
- sl
- es
- sv
- tr
- uk



Lumen	Priming Volume* (mL)	Gravity Flow Rate† (mL/hr)
Distal (16 Ga.)	0.58	2689
Medial 1 (14 Ga.)	0.69	4100
Medial 2 (18 Ga.)	0.43	863
Medial 3 (20 Ga.)	0.43	640
Proximal (18 Ga.)	0.48	921

\* Priming volumes are approximate and are done without accessories.

† Flow rate values are approximate and are determined using deionized water at 100 cm head height.

EU Authorized Representative and Importer:

**EC REP** Teleflex Medical  
 IDA Business and Technology Park  
 Dublin Road, Athlone  
 Co. Westmeath, Ireland  
 2797

**Arrow International LLC**  
 Subsidiary of Teleflex Incorporated  
 3015 Carrington Mill Blvd.  
 Morrisville, NC 27560 USA

**Teleflex®**  
[www.teleflex.com](http://www.teleflex.com)

LBL055301 R01 (2023-09)

LOT



9.5 Fr. 5 Lumen 30 cm catheter length .032 inch dia. spring-wire guide

REF EU-14955-CVT

# Five-Lumen CVC