

Dimensions:  
Width: 8-3/4" (22,2 cm)  
Length: 11-1/8" (28,3 cm)

**PB-10001-000A**  
**PBZ-10001-000A**

T-12703-100C  
Width: 8.7598 in = 222.5mm  
Length: 10.374 in = 263.5mm

Product of XXX  
Packaged in XXX

**ARROW**



REF PR-45041-HP

(IPNXXXXXX)

**4.5** Fr. **1** Lumen **50** cm catheter length **.018** inch dia. spring-wire guide

# Pressure Injectable Arrowgard Blue Advance® One-Lumen PICC

**Contents:**

- 1: One Lumen TaperFree® Catheter with Arrowgard Blue Advance® Antimicrobial/Antithrombogenic Protection<sup>1</sup>: 4.5 Fr. (1.58 mm OD) x 50 cm, Pressure Injectable, Blue FlexTip®
- 1: GlideThru™ Peel-Away Sheath: 5 Fr. x 4" (10 cm) Radiopaque over 5 Fr. Dilator
- 1: Spring-Wire Guide: .018" (0.46 mm) dia. x 17-3/4" (45 cm) (Straight Soft Tip on Both Ends)
- 1: Introducer Needle: Echogenic 21 Ga. x 2-3/4" (7 cm) TW
- 1: Syringe: 5 mL Luer-Lock
- 1: Dust Cap: Non-Vented
- 1: SecondSite™ Adjustable Hub: Catheter Clamp
- 1: SecondSite™ Adjustable Hub: Fastener
- 1: Patient ID Card
- 1: Chart Sticker
- 1: Patient Information Booklet
- 1: Checklist/CLIP Sheet
- 1: Paper Tape Measure
- 1: Dressing: STATLOCK®<sup>2</sup> PICC Plus Catheter Stabilization Device

**Rx only**

**Warning: Read all package insert warnings, precautions, and instructions prior to use. Failure to do so may result in severe patient injury or death. www.teleflex.com/IFU California Prop. 65**

**⚠ WARNING:** Cancer and Reproductive Harm.  
www.P65Warnings.ca.gov

**Not made with natural rubber latex.**

Store below 25°C (77°F). Avoid excessive heat above 30°C (86°F).

Fluid path components are non-pyrogenic.

**Contraindications: The Pressure Injectable Arrowgard Blue Advance antimicrobial/antithrombogenic catheter is contraindicated:**

- for patients with known hypersensitivity to chlorhexidine
- in the presence of device related infection in the intended insertion vessel or catheter pathway
- in the presence of thrombosis in the intended insertion vessel or catheter pathway

<sup>1</sup>Licensed under US Patent No. 7,329,412.

<sup>2</sup>A registered trademark of C. R. Bard, Inc.



Lumen	Priming Volume* (mL)	Gravity Flow Rate† (mL/hr)	Pump Flow Rate‡ (mL/hr)	MAX Pressure Injection Flow Rate** (mL/sec)
Distal (17 Ga.)	0.57	1004	5870	5

\* Priming volumes are approximate and are done without accessories.

† Flow rate values are approximate and are determined using deionized water at 100 cm head height.

‡ Pump flow rates are determined at maximum pump pressure of 10 psig and represent approximate flow capabilities.

\*\* Pressure injection flow rates are determined at the injector pressure setting of 300 psi maximum using media of 11.8 centipoise viscosity, with 152 cm pressure tubing.

**LOT** LotNumber

YYYY-MM-DD

YYYY-MM-DD



(01)XXXXXXXXXXXXXX  
(17)YYMMDD  
(11)YYMMDD  
(10)LotNumber

Arrow International LLC  
Subsidiary of Teleflex Incorporated  
3015 Carrington Mill Blvd.  
Morrisville, NC 27560 USA

**Teleflex**  
www.teleflex.com

LBL057480 R01 (2024-03)



# Pressure Injectable Arrowgard Blue Advance® One-Lumen PICC

**ARROW**

REF PR-45041-HP

**4.5** Fr. **1** Lumen **50** cm catheter length **.018** inch dia. spring-wire guide