

Dimensions:
Width: 8-3/4" (22,2 cm)
Length: 11-1/8" (28,3 cm)

PB-10001-000A
PBZ-10001-000A

T-12703-100C
Width: 8.7598 in = 222.5mm
Length: 10.374 in = 263.5mm

ARROW



PR-45541-HP

(IPNXXXXXX)

4.5 Fr. **1** Lumen

55 cm catheter length

.018 inch dia. spring-wire guide

Pressure Injectable Arrowg+ard Blue Advance® One-Lumen PICC

Contents:

- 1: One Lumen TaperFree® Catheter with Arrowg+ard Blue Advance® Antimicrobial/Antithrombogenic Protection†: 4.5 Fr. (1.58 mm OD) x 55 cm, Pressure Injectable, Blue FlexTip®
- 1: GlideThru™ Peel-Away Sheath: 5 Fr. x 4" (10 cm) Radiopaque over 5 Fr. Dilator
- 1: Spring-Wire Guide: .018" (0.46 mm) dia. x 17-3/4" (45 cm) (Straight Soft Tip on Both Ends)
- 1: Introducer Needle: Echogenic 21 Ga. x 2-3/4" (7 cm) TW
- 1: Syringe: 5 mL Luer-Lock
- 1: Dust Cap: Non-Vented
- 1: SecondSite™ Adjustable Hub: Catheter Clamp
- 1: SecondSite™ Adjustable Hub: Fastener
- 1: Patient ID Card
- 1: Chart Sticker
- 1: Patient Information Booklet
- 1: Checklist/CLIP Sheet
- 1: Paper Tape Measure
- 1: Dressing: STATLOCK®² PICC Plus Catheter Stabilization Device

†Licensed under US Patent No. 7,329,412.
²A registered trademark of C. R. Bard, Inc.

Rx only

Warning: Read all package insert warnings, precautions, and instructions prior to use. Failure to do so may result in severe patient injury or death.
www.teleflex.com/IFU

California Prop. 65

⚠ **WARNING:** Cancer and Reproductive Harm.
www.P65Warnings.ca.gov

Not made with natural rubber latex.

Store below 25°C (77°F). Avoid excessive heat above 30°C (86°F).
 Fluid path components are non-pyrogenic.

Contraindications: The Pressure Injectable Arrowg+ard Blue Advance

- antimicrobial/antithrombogenic catheter is contraindicated:
- for patients with known hypersensitivity to chlorhexidine
- in the presence of device related infection in the intended insertion vessel or catheter pathway
- in the presence of thrombosis in the intended insertion vessel or catheter pathway



Lumen	Priming Volume* (mL)	Gravity Flow Rate† (mL/hr)	Pump Flow Rate†† (mL/hr)	MAX Pressure Injection Flow Rate** (mL/sec)
Distal (17 Ga.)	0.59	913	5130	5

* Priming volumes are approximate and are done without accessories.
 † Flow rate values are approximate and are determined using deionized water at 100 cm head height.
 †† Pump flow rates are determined at maximum pump pressure of 10 psig and represent approximate flow capabilities.
 ** Pressure injection flow rates are determined at the injector pressure setting of 300 psi maximum using media of 11.8 centipoise viscosity, with 152 cm pressure tubing.

LOT Lot Number

YYYY-MM-DD

YYYY-MM-DD



(01)XXXXXXXXXXXXXX
 (17)YYMMDD
 (11)YYMMDD
 (10)Lot Number

Product of xxx
 Packaged in xxx

Arrow International LLC
 Subsidiary of Teleflex Incorporated
 3015 Carrington Mill Blvd.
 Morrisville, NC 27560 USA

Teleflex
www.teleflex.com

LBL057483 R01 (2025-01)



Pressure Injectable Arrowg+ard Blue Advance® One-Lumen PICC

ARROW

REF PR-45541-HP

4.5 Fr. **1** Lumen

55 cm catheter length

.018 inch dia. spring-wire guide