



JRT-43541-HPHNM

(IPNXXXXXX)

4.5 Fr.

1 Lumen

35 cm catheter length

.018 inch dia. spring-wire guide

Pressure Injectable Arrowg+ard Blue Advance® One-Lumen JACC with 80 cm Hydrophilic-Coated Nitinol Guidewire

Contents:

- 1: One-Lumen TaperFree® Catheter with Arrowg+ard Blue Advance® Antimicrobial/Antithrombogenic Protection¹: 4.5 Fr. (1.55 mm OD) x 35 cm, Pressure Injectable
- 1: GlideThru™ Peel-Away Sheath: 4.5 Fr. x 4" (10 cm) Radiopaque over 4.5 Fr. Dilator
- 1: Spring-Wire Guide, Nitinol, Marked: .018" (0.46 mm) dia. x 17-3/4" (45 cm) (Straight Soft Tip on One End - Straight Stiff Tip on Other)
- 1: Guidewire, Marked: .018" (0.46 mm) dia. x 80 cm Hydrophilic-Coated Nitinol with Soft Tip Tungsten Coil (CE 0120)
- 1: Introducer Needle: Echogenic 21 Ga. x 2-3/4" (7 cm) TW
- 1: Syringe: 10 mL Luer-Lock
- 1: Dust Cap: Non-Vented
- 1: SecondSite™ Adjustable Hub: Catheter Clamp
- 1: SecondSite™ Adjustable Hub: Fastener
- 1: Catheter Trimmer
- 1: Safety Scalpel: #11
- 1: TightTrack™ Tunnelers: 9" Stainless Steel
- 1: Patient ID Card
- 1: Chart Sticker
- 1: Patient Information Booklet
- 1: Paper Tape Measure
- 1: Dressing: Tegaderm®² 10 cm x 12 cm

¹Licensed under US Patent Nos. 6,706,024, 6,872,195 and 7,329,412.

²A registered trademark of 3M Company.

Rx only

Warning: Read all package insert warnings, precautions, and instructions prior to use. Failure to do so may result in severe patient injury or death. www.teleflex.com/IFU

California Prop. 65

WARNING: Cancer and Reproductive Harm.

www.P65Warnings.ca.gov

Not made with natural rubber latex.

Store below 25°C (77°F). Avoid excessive heat above 30°C (86°F).

Sterilized using ethylene oxide unless otherwise indicated in the contents list.

Fluid path components are non-pyrogenic.

Contraindications: The Arrowg+ard Blue Advance antimicrobial/antithrombogenic catheter is contraindicated for patients with known hypersensitivity to chlorhexidine.



Lumen

Priming Volume* (mL)

Gravity Flow Rate† (mL/hr)

Pump Flow Rate†† (mL/hr)

MAX Pressure Injection Flow Rate** (mL/sec)

Distal (17 Ga.)

0.44

1337

5913


5

* Priming volumes are approximate and are done without accessories.

† Flow rate values are approximate and are determined using deionized water at 100 cm head height.

†† Pump flow rates are determined at maximum pump pressure of 10 psig and represent approximate flow capabilities.

** Pressure injection flow rates are determined using media of 11.8 centipoise (cP) viscosity, with 152 cm administration set tubing.



LOT LotNumber

YYYY-MM-DD

YYYY-MM-DD



(01)XXXXXXXXXXXXXX
(17)YYMMDD
(11)YYMMDD
(10)LotNumber

Arrow International LLC
Subsidiary of Teleflex Incorporated
3015 Carrington Mill Blvd.
Morrisville, NC 27560 USA

Product of xxx
Packaged in xxx

Teleflex®
www.teleflex.com

LBL057541 R02 (2024-04)