



REF JRT-43563-HPHNM (IPNXXXXXX)

6 Fr. 3 Lumen 35 cm catheter length .018 inch dia. spring-wire guide

# Pressure Injectable Arrowgard Blue Advance® Three-Lumen JACC with 80 cm Hydrophilic-Coated Nitinol Guidewire

**Contents:**

- 1: Three-Lumen TaperFree® Catheter with Arrowgard Blue Advance® Antimicrobial/Antithrombogenic Protection<sup>1</sup>: 6 Fr. (2.09 mm OD) x 35 cm, Pressure Injectable
  - 1: GlideThru™ Peel-Away Sheath: 6 Fr. x 4" (10 cm) Radiopaque over 6 Fr. Dilator
  - 1: Spring-Wire Guide, Nitinol, Marked: .018" (0.46 mm) dia. x 17-3/4" (45 cm) (Straight Soft Tip on One End - Straight Stiff Tip on Other)
  - 1: Guidewire, Marked: .018" (0.46 mm) dia. x 80 cm Hydrophilic-Coated Nitinol with Soft Tip Tungsten Coil (CE 0120)
  - 1: Introducer Needle: Echogenic 21 Ga. x 2-3/4" (7 cm) TW
  - 1: Syringe: 10 mL Luer-Lock
  - 3: Dust Cap: Non-Vented
  - 1: SecondSite™ Adjustable Hub: Fastener
  - 1: SecondSite™ Adjustable Hub: Catheter Clamp
  - 1: Catheter Trimmer
  - 1: Safety Scalpel: #11
  - 1: TightTrack™ Tunneler: 9" Stainless Steel
  - 1: Patient ID Card
  - 1: Chart Sticker
  - 1: Patient Information Booklet
  - 1: Paper Tape Measure
  - 1: Dressing: Tegaderm®<sup>2</sup> 10 cm x 12 cm
- <sup>1</sup>Licensed under US Patent No. 7,329,412.  
<sup>2</sup>A registered trademark of 3M Company.

**Rx only**  
**Warning: Read all package insert warnings, precautions, and instructions prior to use. Failure to do so may result in severe patient injury or death.**

California Prop. 65  
**WARNING:** Cancer and Reproductive Harm.  
[www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

**Not made with natural rubber latex.**  
Store below 25°C (77°F). Avoid excessive heat above 30°C (86°F).


Sterilized using ethylene oxide unless otherwise indicated in the contents list.  
Fluid path components are non-pyrogenic.

**Contraindications: The Arrowgard Blue Advance antimicrobial/antithrombogenic catheter is contraindicated for patients with known hypersensitivity to chlorhexidine.**



Lumen	Priming Volume* (mL)	Gravity Flow Rate† (mL/hr)	Pump Flow Rate‡ (mL/hr)	MAX Pressure Injection Flow Rate** (mL/sec)
Distal (17 Ga.)	0.54	1276	6236	6
Medial (19 Ga.)	0.38	140	1249	not rated
Proximal (19 Ga.)	0.38	140	1249	not rated

\* Priming volumes are approximate and are done without accessories.  
† Flow rate values are approximate and are determined using deionized water at 100 cm head height.  
‡ Pump flow rates are determined at maximum pump pressure of 10 psig and represent approximate flow capabilities.  
\*\* Pressure injection flow rates are determined using media of 11.8 centipoise (cP) viscosity, with 152 cm administration set tubing.



LOT LotNumber

YYYY-MM-DD

YYYY-MM-DD



(01)XXXXXXXXXXXXXX  
(17)YYMMDD  
(11)YYMMDD  
(10)LotNumber

Arrow International LLC  
Subsidiary of Teleflex Incorporated  
3015 Carrington Mill Blvd.  
Morrisville, NC 27560 USA

**Teleflex**  
www.teleflex.com