



REF AW-04200-N

.035 inch dia. spring-wire guide

45 cm spring-wire guide

Nitinol Marked Spring-Wire Guide with Arrow® GlideWheel™ Wire Advancer Maximum OD per ISO 11070 is 0.89 mm.

Contents:

- 1: Spring-Wire Guide, Nitinol, Marked: .035" (0.89 mm) dia. x 17-3/4" (45 cm) (Straight Soft Tip on One End - "J" Tip on Other) with Arrow® GlideWheel™ Wire Advancer

Rx only Warning: Read all package insert warnings, precautions, and instructions prior to use. Failure to do so may result in severe patient injury or death. www.teleflex.com/IFU California Prop. 65

⚠ WARNING: Cancer and Reproductive Harm.
www.P65Warnings.ca.gov

Not made with natural rubber latex. Fluid path components are non-pyrogenic.



LOT



Arrow International LLC
 Subsidiary of Teleflex Incorporated
 3015 Carrington Mill Blvd.
 Morrisville, NC 27560 USA

Teleflex®
www.teleflex.com

LBL061026 R00 (2022-02)



REF AW-04200-N

.035 inch dia. spring-wire guide

45 cm spring-wire guide

Nitinol Marked Spring-Wire Guide with Arrow® GlideWheel™ Wire Advancer Maximum OD per ISO 11070 is 0.89 mm.

Contents:

- 1: Spring-Wire Guide, Nitinol, Marked: .035" (0.89 mm) dia. x 17-3/4" (45 cm) (Straight Soft Tip on One End - "J" Tip on Other) with Arrow® GlideWheel™ Wire Advancer

Rx only Warning: Read all package insert warnings, precautions, and instructions prior to use. Failure to do so may result in severe patient injury or death. www.teleflex.com/IFU California Prop. 65

⚠ WARNING: Cancer and Reproductive Harm.
www.P65Warnings.ca.gov

Not made with natural rubber latex. Fluid path components are non-pyrogenic.



LOT



Arrow International LLC
 Subsidiary of Teleflex Incorporated
 3015 Carrington Mill Blvd.
 Morrisville, NC 27560 USA

Teleflex®
www.teleflex.com

LBL061026 R00 (2022-02)