



REF PR-32041-BAS

4 Fr.

1 Lumen

20 cm catheter length

.018 inch dia. spring-wire guide

# Pressure Injectable One-Lumen Midline

## Contents:

- 1: TaperFree® Catheter††: 4 Fr. (1.45 mm OD) x 20 cm Pressure Injectable Radiopaque Polyurethane with Extension Line Clamp and Contamination Guard
- 1: GlideThru™ Peel-Away Sheath: 4 Fr. x 2-3/4" (7 cm) Radiopaque over 4 Fr. Dilator
- 1: Spring-Wire Guide, Nitinol, Marked: .018" (0.46 mm) dia. x 17-3/4" (45 cm) (Straight Soft Tip on One End - Straight Stiff Tip on Other)
- 1: Introducer Needle: Echogenic 21 Ga. x 2-3/4" (7 cm) TW
- 1: Syringe: 10 mL Luer-Lock
- 1: Dust Cap: Non-Vented
- 1: SharpsAway® Disposal Cup
- 1: SharpsAway® II Locking Disposal Cup
- 1: Catheter Trimmer
- 1: Safety Scalpel: #11
- 1: Overbed Sign
- 1: Patient Information Booklet
- 1: Paper Tape Measure
- 1: Dressing: STATLOCK®¹ PICC Plus Catheter Stabilization Device

¹A registered trademark of C. R. Bard, Inc.

## Rx only

**Warning:** Read all package insert warnings, precautions, and instructions prior to use. Failure to do so may result in severe patient injury or death. [www.teleflex.com/IFU](http://www.teleflex.com/IFU)

California Prop. 65

⚠ **WARNING:** Cancer and Reproductive Harm.[www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

\*\*\*MR Safe

Not made with natural rubber latex.

Fluid path components are non-pyrogenic.



Lumen

Priming Volume\* (mL)

Gravity Flow Rate† (mL/hr)

Pump Flow Rate†† (mL/hr)

MAX Pressure Injection Flow Rate\*\* (mL/sec)

Yellow (18 Ga.)

0.37

1880

9324

5

\* Priming volumes are approximate and are done without accessories.

† Flow rate values are approximate and are determined using deionized water at 100 cm head height.

†† Pump flow rates are determined at maximum pump pressure of 10 psig and represent approximate flow capabilities.

\*\* Pressure injection flow rates are determined using media of 11.8 centipoise (cP) viscosity, with 152 cm administration set tubing.



en

fr-CA

pt-BR

es-MX



Arrow International LLC  
Subsidiary of Teleflex Incorporated  
3015 Carrington Mill Blvd.  
Morrisville, NC 27560 USA

**teleflex®**  
[www.teleflex.com](http://www.teleflex.com)

LBL061680 R02 (2022-07)