

Product of xxx Packaged in xxx









(IPNXXXXXX)

Pressure Injectable Two-Lumen Midline

Contents:

- Two-Lumen TaperFree® Catheter‡‡‡: 5 Fr.(1.81 mm OD) x 20 cm Pressure Injectable Radiopaque Polyurethane with Extension Line Clamps and Contamination Guard
- GlideThru™ Peel-Away Sheath: 5 Fr. x 2-3/4" (7 cm) Radiopaque over 5 Fr. Dilator Spring-Wire Guide, Nitinol, Marked: .018" (0.46 mm) dia. x 17-3/4" (45 cm) (Straight Soft Tip on One End - Straight Stiff Tip on Other)
- Introducer Needle: Echogenic 21 Ga. x 2-3/4" (7 cm) TW
- Syringe: 10 mL Luer-Lock
- Dust Cap: Non-Vented
- SharpsAway® II Locking Disposal Cup SharpsAway® Disposal Cup
- Catheter Trimmer
- Safety Scalpel: #11
- Overbed Sign
- Patient Information Booklet
- Paper Tape Measure
- Dressing: STATLOCK®1 PICC Plus Catheter Stabilization Device
- ¹A registered trademark of C. R. Bard, Inc.

Rx	on	ly
----	----	----

Warning: Read all package insert warnings, precautions, and instructions prior to use. Failure to do so may result in severe patient injury or death. www.teleflex.com/IFU

California Prop. 65

▲ WARNING: Cancer and Reproductive Harm.

www.P65Warnings.ca.gov

+++MR Safe

Not made with natural rubber latex.

Fluid path components are non-pyrogenic.

Lumen	Priming Volume* (mL)	Gravity Flow Rate† (mL/hr)	Pump Flow Rate†† (mL/hr)	MAX Pressure Injection Flow Rate** (mL/sec)
Yellow (18 Ga.)	0.36	1170	6809	5
White (18 Ga.)	0.36	1159	6975	5

^{*} Priming volumes are approximate and are done without accessories.















(11)YYMMDD

(10)LotNumber



















[†] Flow rate values are approximate and are determined using deionized water at 100 cm head height.

rietight.
†† Pump flow rates are determined at maximum pump pressure of 10 psig and represent approximate flow capabilities.
** Pressure injection flow rates are determined using media of 11.8 centipoise (cP) viscosity, with 152 cm administration set tubing.