



REF EU-45854-HPS

8.5 Fr. 4 Lumen 20 cm catheter length .032 inch dia. spring-wire guide

Pressure Injectable Arrowg+ard Blue Plus® Four-Lumen CVC

Contents:

- 1: Arrowg+ard Blue Plus®¹ Four-Lumen Catheter: 8.5 Fr. (3.0 mm OD) x 20 cm, Pressure Injectable
- 1: Spring-Wire Guide, Nitinol, Marked: .032" (0.81 mm) dia. x 23-5/8" (60 cm) (Straight Soft Tip on One End - "J" Tip on Other) with Arrow Advancer with ECG Mark
- 1: Introducer Needle: Echogenic 18 Ga. x 2-1/2" (6.35 cm) XTW
- 1: Syringe: 5 mL Luer-Slip
- 1: Tissue Dilator: 9 Fr. x 10.2 cm
- 4: Dust Cap: Non-Vented
- 1: SecondSite™ Adjustable Hub: Fastener
- 1: SecondSite™ Adjustable Hub: Catheter Clamp
- 1: SharpsAway® II Locking Disposal Cup
- 1: Safety Scalpel: #11

Warning: Read all package insert warnings, precautions, and instructions prior to use. Failure to do so may result in severe patient injury or death. www.teleflex.com/IFU

Not made with natural rubber latex.
Store below 25°C (77°F). Avoid excessive heat above 40°C (104°F). Fluid path components are non-pyrogenic.

Contraindications: The Arrowg+ard Blue Plus antimicrobial catheter is contraindicated for patients with known hypersensitivity to chlorhexidine, silver sulfadiazine and/or sulfa drugs.

¹Licensed under US Patent No. 7,329,412.

All components are CE 2797 unless otherwise noted.



CAS # 7440-48-4



Lumen	Priming Volume* (mL)	Gravity Flow Rate† (mL/hr)	MAX Pressure Injection Flow Rate** (mL/sec)
Distal (16 Ga.)	0.40	2283	5
Medial 1 (14 Ga.)	0.50	4316	10
Medial 2 (18 Ga.)	0.36	1079	not rated
Proximal (18 Ga.)	0.39	1162	not rated

* Priming volumes are approximate and are done without accessories.

† Flow rate values are approximate and are determined using deionized water at 100 cm head height.

** Pressure injection flow rates are determined using media of 11.8 centipoise (cP) viscosity, with 152 cm administration set tubing.

EU Authorized Representative and Importer:

Teleflex Medical
IDA Business and Technology Park
Dublin Road, Athlone
Co. Westmeath, Ireland

Arrow International LLC
Subsidiary of Teleflex Incorporated
3015 Carrington Mill Blvd.
Morrisville, NC 27560 USA

Teleflex®
www.teleflex.com

LBL062507 R01 (2023-11)

LOT



8.5 Fr. 4 Lumen 20 cm catheter length .032 inch dia. spring-wire guide

REF EU-45854-HPS

Pressure Injectable Arrowg+ard Blue Plus® Four-Lumen CVC