ARROW®

AGB Antimicrobial

CVC 3 LUMEN

REF CDA-25123-1A   (IPNXXXXXX)

12 Fr.   **3** Lumen   **20** cm catheter length   **.035** inch dia. spring-wire guide

Arrowg+ard Blue® Large-Bore Three-Lumen CVC for High Volume Infusions

Contents:

1: Arrowg+ard Blue® Three-Lumen Catheter: 12 Fr. (4.1 mm OD) x 20 cm
1: Spring-Wire Guide, Marked: .035" (0.89 mm) dia. x 26-3/4" (68 cm) (Straight Soft Tip on One End - "J" Tip on Other) with Arrow Advancer
1: Catheter: 18 Ga. x 2-1/2" (6.35 cm) Radiopaque over 20 Ga. RW Introducer Needle
1: Pressure Transduction Probe
1: Introducer Needle: Echogenic 18 Ga. x 2-1/2" (6.35 cm) XTW and 5 mL Arrow® Raulerson Spring-Wire Introduction Syringe
1: Injection Needle: Eclipse™[1] 23 Ga. x 1-1/2" (3.81 cm) and 5 mL Luer-Slip Syringe
1: Injection Needle: Eclipse™[1] 25 Ga. x 1" (2.54 cm) and 3 mL Luer-Lock Syringe
1: Syringe: 10 mL Luer-Lock
1: Tissue Dilator: 10 Fr. (3.5 mm) x 10.2 cm
1: Tissue Dilator: 12 Fr. (4.0 mm) x 14 cm
1: SharpsAway® II Locking Disposal Cup
1: SharpsAway® Disposal Cup
1: Maximal Barrier Drape™ with 4" fenestration
1: Towel
1: Needle Holder
1: Forceps
1: Safety Scalpel: #11
1: Checklist/CLIP Sheet
1: Sterile Procedure Sign
2: Gauze Pad: 2" x 2" (5 cm x 5 cm)
5: Gauze Pad: 4" x 4" (10 cm x 10 cm)
1: Dressing: Tegaderm®[2] 10 cm x 12 cm
1: Surgical Apparel: Impervious Gown

1: Surgical Apparel: Bouffant Cap
1: Surgical Apparel: Mask with Eye Shield
1: Suture: 3-0 Silk with Curved Needle
1: HemoHopper® Fluid Receptacle

[1]A trademark of Becton, Dickinson and Company.
[2]A registered trademark of 3M Company.

Not made with natural rubber latex.
Store below 25°C (77°F). Avoid excessive heat above 40°C (104°F).

Contraindications: The Arrowg+ard Blue antimicrobial catheter is contraindicated for patients with known hypersensitivity to chlorhexidine, silver sulfadiazine and/or sulfa drugs.

Lumen	Priming Volume* (mL)	Gravity Flow Rate† (mL/hr)
Distal (16 Ga.)	0.40	2457
Medial (12 Ga.)	1.3	10151
Proximal (12 Ga.)	1.2	11039

* Priming volumes are approximate and are done without accessories.
† Flow rate values are approximate and are determined using deionized water at 100 cm head height.

LATEX   25°C (77°F)