







spring-wire guide



## Pressure Injectable Arrowg+ard Blue Advance® Three-Lumen PICC



## Contents:

- Three Lumen TaperFree® Catheter with Arrowg+ard Blue Advance® Antimicrobial/Antithrombogenic Protection1: 6 Fr. (2.11 mm OD) x 55 cm,
- Pressure Injectable, T-Port Connector, Blue FlexTip® and Placement Wire
- GlideThru™ Peel-Away Sheath: 6 Fr. x 2-3/4" (7 cm) Radiopague over 6 Fr.
- Spring-Wire Guide, Nitinol, Marked: .018" (0.46 mm) dia. x 17-3/4" (45 cm) (Straight Soft Tip on One End - Straight Stiff Tip on Other) with Arrow
- Injection Needle: Eclipse™2 25 Ga. x 1" (2.54 cm)
- Safety Introducer Needle: Echogenic 21 Ga. x 2-3/4" (7 cm) TW
- Introducer Needle: Echogenic 21 Ga, x 2-3/4" (7 cm) TW
- Syringe: 10 mL Luer-Lock
- Syringe: 3 mL Luer-Lock
- Dust Cap: Non-Vented
- SecondSite™ Adjustable Hub: Fastener
- SecondSite™ Adjustable Hub: Catheter Clamp
- SharpsAway® II Locking Disposal Cup
- SharpsAway® Disposal Cup
- Catheter Trimmer
- Towel: 24" x 36" (61 cm x 91 cm)
- Maximal Barrier Drape™ with two 13 cm (5") x 15 cm (6") fenestrations
- Safety Scalpel: #11
- Patient ID Card
- Patient Information Booklet
- Paper Tape Measure
- Tourniquet
- Gauze Pad: 2" x 2" (5 cm x 5 cm)
- Gauze Pad: 4" x 4" (10 cm x 10 cm)
- Dressing: Tegaderm®3 15.5 cm x 10 cm
- Surgical Apparel: Impervious Gown

- Dressing: STATLOCK®4 Catheter Stabilization Device
- Surgical Apparel: Mask with Eye Shield
- Surgical Apparel: Bouffant Cap

55 cm catheter length

- 1: Surgical Apparel: Mask
- Tape: Steri-Strip®3
- HemoHopper® Fluid Receptacle
- <sup>1</sup>Licensed under US Patent No. 7,329,412.
- <sup>2</sup>A trademark of Becton, Dickinson and Company.
- <sup>3</sup>A registered trademark of 3M Company.
- <sup>4</sup>A registered trademark of C. R. Bard, Inc.

All components are CE 2797 unless otherwise noted.



## Not made with natural rubber latex.

Store below 25°C (77°F). Avoid excessive heat above 30°C (86°F).

Contraindications: The Pressure Injectable Arrowg+ard Blue Advance antimicrobial/antithrombogenic catheter is

- for patients with known hypersensitivity to chlorhexidine
- in the presence of device related infection in the intended insertion vessel or catheter pathway
- in the presence of thrombosis in the intended insertion vessel or catheter pathway


Lumen	Priming Volume* (mL)	Gravity Flow Rate† (mL/hr)	Pump Flow Rate†† (mL/hr)	MAX Pressure Injection Flow Rate** (mL/sec)
Distal (18 Ga.) Medial (19 Ga.)	0.61 0.45	880 244	5360 2090	6 not rated
Proximal (19 Ga.)	0.47	257	2160	not rated

<sup>\*</sup> Priming volumes are approximate and are done without accessories.

- † Flow rate values are approximate and are determined using deionized water at 100 cm head
- †† Pump flow rates are determined at maximum pump pressure of 10 psig and represent approximate flow capabilities.
- \*\* Pressure injection flow rates are determined at the injector pressure setting of 300 psi maximum using media of 11.8 centipoise viscosity, with 152 cm pressure tubing.







LBL069834 R01 (2024-01)