



REF PR-45552-HP (IPNXXXXXX)

5.5 Fr. 2 Lumen 55 cm catheter length .018 inch dia. spring-wire guide

# Pressure Injectable Arrowgard Blue Advance® Two-Lumen PICC

**Contents:**

- 1: Two Lumen TaperFree® Catheter††† with Arrowgard Blue Advance® Antimicrobial/Antithrombotic Protection†: 5.5 Fr. (1.88 mm OD) x 55 cm Pressure Injectable and Contamination Guard
- 1: GlideThru™ Peel-Away Sheath: 5.5 Fr. x 4" (10 cm) Radiopaque over 5.5 Fr. Dilator
- 1: Spring-Wire Guide: .018" (0.46 mm) dia. x 17-3/4" (45 cm) (Straight Soft Tip on Both Ends)
- 1: Introducer Needle: Echogenic 21 Ga. x 2-3/4" (7 cm) TW
- 1: Syringe: 5 mL Luer-Lock
- 2: Dust Cap: Non-Vented
- 1: Patient ID Card
- 1: Patient Information Booklet
- 1: Paper Tape Measure
- 1: Dressing: STATLOCK®2 PICC Plus Catheter Stabilization Device

†Licensed under US Patent No. 7,329,412 and 11,219,706.

‡A registered trademark of C. R. Bard, Inc.

All components are CE 2797 unless otherwise noted.

**Rx only**

**Warning:** Read all package insert warnings, precautions, and instructions prior to use. Failure to do so may result in severe patient injury or death. [www.teleflex.com/IFU](http://www.teleflex.com/IFU)

California Prop. 65

⚠ **WARNING:** Cancer and Reproductive Harm.

[www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

###MR Safe

Not made with natural rubber latex.

Store below 25°C (77°F). Avoid excessive heat above 30°C (86°F).

Fluid path components are non-pyrogenic.

**Contraindications: The Pressure Injectable Arrowgard Blue Advance antimicrobial/antithrombotic catheter is contraindicated:**

- for patients with known hypersensitivity to chlorhexidine
- in the presence of device related infection in the intended insertion vessel or catheter pathway
- in the presence of thrombosis in the intended insertion vessel or catheter pathway



Lumen

	Priming Volume* (mL)	Gravity Flow Rate† (mL/hr)	Pump Flow Rate†† (mL/hr)	MAX Pressure Injection Flow Rate** (mL/sec)
Pink (18 Ga.)	0.56	350	3050	5
White (18 Ga.)	0.58	360	3100	5

\* Priming volumes are approximate and are done without accessories.

† Flow rate values are approximate and are determined using deionized water at 100 cm head height.

†† Pump flow rates are determined at maximum pump pressure of 10 psig and represent approximate flow capabilities.

\*\* Pressure injection flow rates are determined at the injector pressure setting of 300 psi maximum using media of 11.8 centipoise viscosity, with 152 cm pressure tubing.



- en
- cs
- da
- nl
- et
- fi
- fr
- de
- el
- it
- no
- pl
- pt
- ro
- ru
- sk
- sl
- es
- sv
- tr



**LOT** LotNumber

YYYY-MM-DD

YYYY-MM-DD



(01)XXXXXXXXXXXXXX  
(17)YYMMDD  
(11)YYMMDD  
(10)LotNumber

CAS # 7440-48-4



EU Authorized Representative and Importer:

**EC REP** Teleflex Medical  
IDA Business and  
Technology Park  
Dublin Road, Athlone  
Co. Westmeath, Ireland  
2797

All components are CE 2797 unless otherwise noted.

Arrow International LLC  
Subsidiary of Teleflex Incorporated  
3015 Carrington Mill Blvd.  
Morrisville, NC 27560 USA

Product of XXX  
Packaged in XXX

**Teleflex®**  
[www.teleflex.com](http://www.teleflex.com)