



REF DLX-45563-HPKB (IPNXXXXXX)

6.0 Fr. 3 Lumen 55 cm catheter length .018 inch dia. spring-wire guide

# Pressure Injectable Arrowgard Blue Advance® Three-Lumen PICC



**Contents:**

- |   |   |
|---|---|
| <ul style="list-style-type: none"> <li>1: Three Lumen TaperFree® Catheter††† with Arrowgard Blue Advance® Antimicrobial/Antithrombotic Protection<sup>1</sup>: 6 Fr. (2.11 mm OD) x 55 cm, Pressure Injectable, Stiffening Stylet (0.36 mm dia. x 75 cm with straight distal tip) and T-Port Connector</li> <li>1: GlideThru™ Peel-Away Sheath: 6 Fr. x 2-3/4" (7 cm) Radiopaque over 6 Fr. Dilator</li> <li>1: Spring-Wire Guide, Nitinol, Marked: .018" (0.46 mm) dia. x 17-3/4" (45 cm) (Straight Soft Tip on One End - Straight Stiff Tip on Other) with Arrow Advancer</li> <li>1: Injection Needle: SafetyGlide™<sup>2</sup> 25 Ga. x 5/8" (1.60 cm) RW</li> <li>1: Safety Introducer Needle: Echogenic 21 Ga. x 2-3/4" (7 cm) TW</li> <li>1: Blunt Fill Needle: 18 Ga. x 1-1/2" (3.81 cm)</li> <li>1: Introducer Needle: Echogenic 21 Ga. x 2-3/4" (7 cm) TW</li> <li>1: Syringe: 5 mL Luer-Lock</li> <li>3: 10 mL Luer-Lock Pre-Filled Saline Syringe</li> <li>1: 5 mL 1% Lidocaine HCl Solution and Alcohol Prep</li> <li>1: 3 mL Applicator 2% CHG and 70% IPA Chloraprep®<sup>3</sup> One-Step Solution</li> <li>2: 3 mL Applicator 2% CHG and 70% IPA Chloraprep®<sup>3</sup> One-Step Solution with Hi-Lite Orange™ Tint</li> <li>3: Dust Cap: Non-Vented</li> <li>1: SharpsAway® Disposal Cup</li> <li>1: SharpsAway® II Locking Disposal Cup</li> <li>1: Catheter Trimmer</li> <li>1: Towel: 24" x 36" (61 cm x 91 cm)</li> <li>1: Maximal Barrier Drape™ with two 13 cm (5") x 15 cm (6") fenestrations</li> <li>1: Safety Scalpel: #11</li> <li>1: Sterile Procedure Sign</li> <li>1: Patient ID Card</li> </ul> | <ul style="list-style-type: none"> <li>1: Patient Information Booklet</li> <li>1: Medication Label: 1% Lidocaine</li> <li>2: Paper Tape Measure</li> <li>1: Tourniquet</li> <li>10: Gauze Pad: 2" x 2" (5 cm x 5 cm)</li> <li>10: Gauze Pad: 4" x 4" (10 cm x 10 cm)</li> <li>1: Surgical Apparel: Impervious Gown</li> <li>1: Dressing: I.V. Advanced 8.5 cm x 11.5 cm</li> <li>1: Dressing: BIOPATCH®<sup>4</sup></li> <li>1: Transducer Cover with Gel and Rubber Bands</li> <li>1: Surgical Apparel: Mask with Eye Shield</li> <li>1: Dressing: STATLOCK®<sup>5</sup> PICC Plus Catheter Stabilization Device</li> <li>1: Surgical Apparel: Bouffant Cap</li> <li>1: Surgical Apparel: Mask</li> <li>1: Tape: Steri-Strip®<sup>6</sup></li> </ul> |
|---|---|

<sup>1</sup>Licensed under US Patent No. 7,329,412 and 11,219,706.  
<sup>2</sup>A trademark of Becton, Dickinson and Company.  
<sup>3</sup>A registered trademark of CareFusion or one of its subsidiaries.  
<sup>4</sup>A registered trademark of Johnson & Johnson Corporation.  
<sup>5</sup>A registered trademark of C. R. Bard, Inc.  
<sup>6</sup>A registered trademark of 3M Company.

**###MR Safe**

Not made with natural rubber latex.

Store between 20 – 25°C (68 – 77°F).

Arrow International provides the enclosed medication label(s) for your convenience. Please ensure that these labels are applied to the correct syringe and corresponding medication.

**Contraindications: The Pressure Injectable Arrowgard Blue Advance antimicrobial/antithrombotic catheter is contraindicated:**

- for patients with known hypersensitivity to chlorhexidine
- in the presence of device related infection in the intended insertion vessel or catheter pathway
- in the presence of thrombosis in the intended insertion vessel or catheter pathway



Lumen

	Priming Volume* (mL)	Gravity Flow Rate† (mL/hr)	Pump Flow Rate†† (mL/hr)	MAX Pressure Injection Flow Rate** (mL/sec)
Pink (18 Ga.)	0.70	990	5440	6
Blue (19 Ga.)	0.52	240	1930	not rated
White (19 Ga.)	0.49	270	2070	not rated

\* Priming volumes are approximate and are done without accessories.

† Flow rate values are approximate and are determined using deionized water at 100 cm head height.

†† Pump flow rates are determined at maximum pump pressure of 10 psig and represent approximate flow capabilities.

\*\* Pressure injection flow rates are determined at the injector pressure setting of 300 psi maximum using media of 11.8 centipoise viscosity, with 152 cm pressure tubing.

