



(IPNXXXXXX)



## **Pressure Injectable One-Lumen Midline**



## Contents:

- TaperFree® Catheter‡‡: 4 Fr.(1.45 mm OD) x 20 cm Pressure Injectable Radiopaque Polyurethane with Extension Line Clamp and Contamination
- GlideThru™ Peel-Away Sheath: 4 Fr. x 2-3/4" (7 cm) Radiopaque over 4 Fr. Dilator
- Spring-Wire Guide, Nitinol, Marked: .018" (0.46 mm) dia. x 17-3/4" (45 cm) (Straight Soft Tip on One End - Straight Stiff Tip on Other) with Arrow Advancer
- Introducer Needle: 21 Ga. x 1-1/2" (3.81 cm) TW
- Injection Needle: Eclipse™1 25 Ga. x 1" (2.54 cm)
- Safety Introducer Needle: Echogenic 21 Ga. x 2-3/4" (7 cm) TW
- Introducer Needle: Echogenic 21 Ga. x 2-3/4" (7 cm) TW
- Filter Needle: 18 Ga. TW x 1-1/2" (3.81 cm) with Blunt Fill Tip
- Syringe: 10 mL Luer-Lock
- Syringe: 3 mL Luer-Lock
- Dust Cap: Non-Vented
- SecondSite™ Adjustable Hub: Catheter Clamp
- SecondSite™ Adjustable Hub: Fastener
- SharpsAway® II Locking Disposal Cup
- SharpsAway® Disposal Cup
- Catheter Trimmer
- Towel: 24" x 36" (61 cm x 91 cm)

Not made with natural rubber latex.

- Maximal Barrier Drape™ with two 13 cm (5") x 15 cm (6") fenestrations
- Safety Scalpel: #11
- Sterile Procedure Sign
- Overbed Sign
- 1: Patient ID Card

- 1: Checklist/CLIP Sheet
- 1: Patient Information Booklet
- Paper Tape Measure
- Tourniquet
- 5: Gauze Pad: 2" x 2" (5 cm x 5 cm)
- 10: Gauze Pad: 4" x 4" (10 cm x 10 cm)
- Surgical Apparel: Impervious Gown
- Dressing: I.V. Advanced 8.5 cm x 11.5 cm
- Transducer Cover with Gel and Rubber Bands
- Surgical Apparel: Bouffant Cap
- Dressing: STATLOCK®2 PICC Plus Catheter Stabilization Device
- Surgical Apparel: Mask with Eye Shield
- Surgical Apparel: Mask
- Tape: Steri-Strip®3
- 1: Valve: MicroCLAVE™4 Neutral Displacement Connector
- <sup>1</sup>A trademark of Becton, Dickinson and Company
- <sup>2</sup>A registered trademark of C. R. Bard, Inc.
- <sup>3</sup>A registered trademark of 3M Company.
- <sup>4</sup>A trademark of ICU Medical, Inc.

Lumen	Priming Volume* (mL)	Gravity Flow Rate† (mL/hr)	Pump Flow Rate†† (mL/hr)	MAX Pressure Injection Flow Rate** (mL/sec)	
Vellow (18 Ga.)	0.37	1880	9324	5	

<sup>\*</sup> Priming volumes are approximate and are done without accessories.





LBL077557 R00 (2025-05)

<sup>†</sup> Flow rate values are approximate and are determined using deionized water at 100 cm head

<sup>††</sup> Pump flow rates are determined at maximum pump pressure of 10 psig and represent

<sup>\*\*</sup> Pressure injection flow rates are determined using media of 11.8 centipoise (cP) viscosity, with 152 cm administration set tubing.