



IMID-32052-MAX

(IPNXXXXXX)

5 Fr.

2 Lumen

20 cm catheter length

.018 inch dia. spring-wire guide

ARROW®

Pressure Injectable Two-Lumen Midline



Contents:

- 1: Two-Lumen TaperFree® Catheter,†††: 5 Fr.(1.81 mm OD) x 20 cm Pressure Injectable Radiopaque Polyurethane with Extension Line Clamps and Contamination Guard

1: GlideThru™ Peel-Away Sheath: 5 Fr. x 2-3/4" (7 cm) Radiopaque over 5 Fr. Dilator

1: Spring-Wire Guide, Nitinol, Marked: .018" (0.46 mm) dia. x 17-3/4" (45 cm) (Straight Soft Tip on One End - Straight Stiff Tip on Other) with Arrow Advancer

1: Introducer Needle: 21 Ga. x 1-1/2" (3.81 cm) TW

1: Injection Needle: Eclipse™1 25 Ga. x 1" (2.54 cm)

1: Safety Introducer Needle: Echogenic 21 Ga. x 2-3/4" (7 cm) TW

1: Introducer Needle: Echogenic 21 Ga. x 2-3/4" (7 cm) TW

1: Filter Needle: 18 Ga. TW x 1-1/2" (3.81 cm) with Blunt Fill Tip

1: Syringe: 10 mL Luer-Lock

1: Syringe: 3 mL Luer-Lock

2: Dust Cap: Non-Vented

1: SecondSite™ Adjustable Hub: Fastener

1: SecondSite™ Adjustable Hub: Catheter Clamp

1: SharpsAway® II Locking Disposal Cup

1: SharpsAway® Disposal Cup

1: Catheter Trimmer

1: Towel: 24" x 36" (61 cm x 91 cm)

1: Maximal Barrier Drape™ with two 13 cm (5") x 15 cm (6") fenestrations

1: Towel

1: Safety Scalpel: #11

1: Sterile Procedure Sign

1: Overbed Sign

1: Patient ID Card
- 1: Checklist/CLIP Sheet

1: Patient Information Booklet

2: Paper Tape Measure

1: Tourniquet

5: Gauze Pad: 2" x 2" (5 cm x 5 cm)

10: Gauze Pad: 4" x 4" (10 cm x 10 cm)

1: Surgical Apparel: Impervious Gown

1: Dressing: I.V. Advanced 8.5 cm x 11.5 cm

1: Transducer Cover with Gel and Rubber Bands

1: Surgical Apparel: Bouffant Cap

1: Dressing: STATLOCK®2 PICC Plus Catheter Stabilization Device

1: Surgical Apparel: Mask with Eye Shield

1: Surgical Apparel: Mask

1: Tape: Steri-Strip®3

2: Valve: MicroCLAVE™4 Neutral Displacement Connector

¹A trademark of Becton, Dickinson and Company.

²A registered trademark of C. R. Bard, Inc.

³A registered trademark of 3M Company.

⁴A trademark of ICU Medical, Inc.

***MR Safe
Not made with natural rubber latex.



Lumen

	Priming Volume* (mL)	Gravity Flow Rate† (mL/hr)	Pump Flow Rate†† (mL/hr)	MAX Pressure Injection Flow Rate** (mL/sec)
Yellow (18 Ga.)	0.36	1170	6809	5
White (18 Ga.)	0.36	1159	6975	5

* Priming volumes are approximate and are done without accessories.
† Flow rate values are approximate and are determined using deionized water at 100 cm head height.
†† Pump flow rates are determined at maximum pump pressure of 10 psig and represent approximate flow capabilities.
** Pressure injection flow rates are determined using media of 11.8 centipoise (cP) viscosity, with 152 cm administration set tubing.



CAS # 7440-48-4

†††

