











- Three Lumen TaperFree® Catheter‡‡‡ with Arrowg+ard Blue Advance® Antimicrobial/Antithrombogenic Protection¹: 6 Fr. (2.11 mm OD) x 55 cm, Pressure Injectable, Arrow® NaviCurve™ Stylet and T-Port Connector
- GlideThru™ Peel-Away Sheath: 6 Fr. x 2-3/4" (7 cm) Radiopaque over 6 Fr.
- Spring-Wire Guide, Nitinol, Marked: .018" (0.46 mm) dia. x 17-3/4" (45 cm)
- (Straight Soft Tip on One End Straight Stiff Tip on Other) with Arrow Advancer Introducer Needle: 21 Ga. x 1-1/2" (3.81 cm) TW
- Injection Needle: Eclipse™2 25 Ga. x 1" (2.54 cm)
- Safety Introducer Needle: Echogenic 21 Ga. x 2-3/4" (7 cm) TW
- Introducer Needle: Echogenic 21 Ga. x 2-3/4" (7 cm) TW
- Filter Needle: 18 Ga. TW x 1-1/2" (3.81 cm) with Blunt Fill Tip
- Svringe: 10 mL Luer-Lock
- Syringe: 3 mL Luer-Lock
- Dust Cap: Non-Vented
- SecondSite™ Adjustable Hub: Fastener
- SecondSite™ Adjustable Hub: Catheter Clamp
- SharpsAway® Disposal Cup
- SharpsAway® II Locking Disposal Cup
- Catheter Trimmer
- Towel: 24" x 36" (61 cm x 91 cm)
- Maximal Barrier Drape™ with two 13 cm (5") x 15 cm (6") fenestrations

Store below 25°C (77°F). Avoid excessive heat above 30°C (86°F)

· for patients with known hypersensitivity to chlorhexidine

- Safety Scalpel: #11
- Patient ID Card
- Sterile Procedure Sign
- 1: Patient Information Booklet

Not made with natural rubber latex.

- 2: Paper Tape Measure
- Tourniquet
- Foam Electrodes (3 per pack)
- 5: Gauze Pad: 2" x 2" (5 cm x 5 cm)
- 10: Gauze Pad: 4" x 4" (10 cm x 10 cm)
- Surgical Apparel: Impervious Gown
- Dressing: I.V. Advanced 8.5 cm x 11.5 cm
- Transducer Cover with Gel and Rubber Bands
- Remote Cover
- Surgical Apparel: Mask with Eye Shield
- Dressing: STATLOCK®3 PICC Plus Catheter Stabilization Device
- Surgical Apparel: Bouffant Cap
- Surgical Apparel: Mask
- Tape: Steri-Strip®4
- 3: Valve: MicroCLAVE™5 Neutral Displacement Connector
- T-Piece Cover
- ¹Licensed under US Patent No. 7,329,412 and 11,219,706.
- ²A trademark of Becton, Dickinson and Company
- 3A registered trademark of C. R. Bard, Inc.
- ⁴A registered trademark of 3M Company.
- 5A trademark of ICU Medical, Inc.

All components are CE 2797 unless otherwise noted.

Lumen	Priming Volume* (mL)	Gravity Flow Rate† (mL/hr)	Pump Flow Rate†† (mL/hr)	MAX Pressure Injection Flow Rate** (mL/sec)
Pink (18 Ga.)	0.70	990	5440	6
Blue (19 Ga.)	0.52	240	1930	not rated
White (19 Ga.)	0.49	270	2070	not rated

^{*} Priming volumes are approximate and are done without accessories.







• in the presence of device related infection in the intended insertion vessel or catheter pathway

· in the presence of thrombosis in the intended insertion vessel or catheter pathway

Contraindications: The Pressure Injectable Arrowg+ard Blue Advance antimicrobial/antithrombogenic catheter is contraindicated:

LBL078812 R00 (2025-04)

[†] Flow rate values are approximate and are determined using deionized water at 100 cm head height.

^{††} Pump flow rates are determined at maximum pump pressure of 10 psig and represent approximate flow capabilities.

^{**} Pressure injection flow rates are determined at the injector pressure setting of 300 psi maximum using media of 11.8 centipoise viscosity, with 152 cm pressure tubing.